

AWNING UNITS & MULL CONFIGURATIONS

2' 6" widths

	2'-6"	5'-0"	7'-6"
FS	2'-6"	5'-0"	7'-6"
RO	2'-6 1/2"	5'-0 1/2"	7'-6 1/2"
GS	24 5/8"	24 5/8"	24 5/8"
1'-8"			
1'-8 1/2"	KU26181	KU26182	KU26183
3'-4"			
3'-4 1/2"	KU26182	KU261822	KU261832
5'-0"			
5'-0 1/2"	KU26183	KU261823	KU261833
2'-0"			
2'-0 1/2"	KU26201	KU26202	KU26203
4'-0"			
4'-0 1/2"	KU26202	KU262022	KU262032
6'-0"			
6'-0 1/2"	KU26203	KU262023	KU262033
2'-6"			
2'-6 1/2"	KU26261	KU26262	KU26263
5'-0"			
5'-0 1/2"	KU26262	KU262622	KU262632
3'-0"			
3'-0 1/2"	KU26301	KU26302	KU26303
6'-0"			
6'-0 1/2"	KU26302	KU263022	KU263032

NOTES: All measurements are nominal. Elevation charts on this file are not to scale.

Venting is viewed from the exterior.

Grilles are optional. The grille configuration shown for single units are typical for each sash of mullied units.

FS=Frame Size RO=Rough Opening GS=Glass Size (Glass sizes are shown per sash)